



1/4-20 UNC-2B X  
.50 DEEP FULL THD.  
4 PLS.

1/4-20 UNC-2B THRU  
4 PLS.

RAE P/N	DAYTON MODEL	VOLTAGE (VDC)	HP	RPM	TORQUE (IN-LBS)	CURRENT (AMPS)	C	L1	L2	WEIGHT
3110087	4Z144	12/24	1/14 / 1/6	1750 / 4200	2.56	6.9	6.41	4.42	4.89	6.3
3130308	4Z143	12/24	1/7 / 1/4	1750 / 3900	5.63	14.0	8.41	6.42	6.89	9.0
3140042	4Z529	12/24	1/6 / 1/3	1800 / 4200	6.38	16.5	9.41	7.42	7.89	10.0
3110086	4Z141	90	1/18	1800	1.95	.75	6.41	4.42	4.89	6.3
3130307	4Z140	90	1/8	1800	4.38	1.50	8.41	6.42	6.89	9.0
3140041	4Z528	90	1/6	1800	5.63	1.80	9.41	7.42	7.89	10.0
3110088	1Z840	180	1/14	2350	1.95	.41	6.41	4.42	4.89	6.3
3130309	1Z842	180	1/8	1800	4.38	.68	8.41	6.42	6.89	9.0
3140043	1Z851	180	1/6	1800	5.63	.90	9.41	7.42	7.89	10.0