

Rae Corporation

4615 W. Prime Pkwy.

Mchenry, IL 60050 7037 US

Phone: 815.385.3500 • Fax: 815.363.1641

E-Mail: raesales@raemotors.com • Web site:www.raemotors.com

Item # G4, Right Angle Gearmotors - G4 Series


The G4 Series Single Worm Reduction Right Angle Gearbox, when matched with the appropriate RAE motor, is designed for applications requiring low output torque. All metal construction with a Bakelite gear provides quiet operation for noise sensitive applications

- Continuous Duty
- Rating up to 7 in- lbs
- Speeds up to 400 rpm
- 12 up to 115 VDC
- 12:1 up to 47:1 Ratios
- 0.250" Maximum Shaft Diameter
- Class "F" Insulation

Gearbox dimensions only. Reference appropriate Series for dimension of motor.

Compatible Motors:

The G4 Series may be combined with the M1500 or M1600 Series motor.



· [FEATURES](#) · [SPECIFICATIONS](#)

FEATURES

- Grease Lubrication
- Sleeve Bearings (Gearbox)
- High Energy Ceramic Magnets
- Double Shielded Ball Bearings (Motor)
- Dynamically Balanced Armature
- 8" Leads
- TENV Design
- Externally Replaceable Brushes
- Auto-Hook Tang Type Commutator
- Value Added Options and Modifications Available

SPECIFICATIONS

Torque Rating	0 up to 7 in·lb
Speeds	0 up to 400 rpm

Voltages	12 up to 115 V
Ratios	12:1 up to 47:1
Max. Shaft Diameter	0.250 in.
Insulation	Class "F"
Lead Length	8 in
