Rae Corporation

4615 W. Prime Pkwy.

Mchenry, IL 60050 7037 US

Phone: 815.385.3500 • Fax: 815.363.1641


E-Mail: raesales@raemotors.com • Web site:www.raemotors.com

Item # M4300 G250, Right Angle Gear Box G250 Series

RAE Corporation has achieved a major breakthrough in design and development of its G250 Right Angle Gearbox. This breakthrough has resulted in a right angle gearbox that has an 80% to 90% efficiency rating very appropriate for applications that require Back Drive.

Bevel gears transmit power from the motor through the gear box more efficiently. This allows higher torques with smaller motors, resulting in savings of power consumption, weight, and total cost.





FEATURES SPECIFICATIONS ELECTRICAL RATING

FEATURES

- High Energy Ceramic Magnets
- Double Shielded Ball Bearings
- Dynamically Balanced Armature
- Reversible Design
- 8" Leads
- TENV Design
- · Round or Square End Bells
- Externally Replaceable Brushes
- Auto-Hook Tang Type Commutator
- Value added options and modifications available

SPECIFICATIONS

Voltage	12 up to 180 V			
Speed	0 up to 3500 rpm			
Continuous Torque DC Rating	98.0 in·oz			
Continuous Torque SCR Rating	50.0 in·oz			
Weight	7.80 lbs			

HP Rating	0 up to 1/5			
Max. Shaft Diameter	0.500 in.			
Standard Pilot Diameter	2.015 in.			
L1	11.705/11.650 in.			
L2	3.12 in.			
Insulation	Class "F"			
Lead Length	8 in			
End Bells	Round or Square			

ELECTRICAL	RATING				
Model	Voltage	Ratio	Amps	Speed	Torque
		92.7:1	15	19	250 in·lb
		81.8:1	1 5	22	250 in·lb
		60:01:00	1.5	30	200 in·lb
M4300/G250	90 VDC	44.2:1	1.5	41	147 in·lb
		31.4:1	1.5	57	105 in·lb

1.5

1.5

23.1:1

10:01

78

180

77 in·lb

36 in·lb